

Photomultiplier tube
R1635



10mm dia., Head-on type, Bialkali photocathode (Effective area : 8 mm dia./Spectral response : 300 to 650 nm)

Specifications

Type	Head-on type
Tube Size	Dia.10 mm
Photocathode Area Shape	Round
Photocathode Area Size	Dia.8 mm
Wavelength (Short)	300 nm
Wavelength (Long)	650 nm
Wavelength (Peak)	420 nm
Spectral Response Curve Code	400K
Photocathode Material	Bialkali
Window Material	Borosilicate glass
Dynode Structure	Linear-focused
Dynode Stages	8
[Max. Rating] Anode to Cathode Voltage	1500 V
[Max. Rating] Average Anode Current	0.03 mA

Anode to Cathode Supply Voltage	1250 V
[Cathode] Luminous Sensitivity Min.	60 $\mu\text{A}/\text{lm}$
[Cathode] Luminous Sensitivity Typ.	100 $\mu\text{A}/\text{lm}$
[Cathode] Blue Sensitivity Index (CS 5-58) Typ.	10.0
[Cathode] Radiant Sensitivity Typ.	80 mA/W
[Anode] Luminous Sensitivity Min.	30 A/lm
[Anode] Luminous Sensitivity Typ.	100 A/lm
[Anode] Radiant Sensitivity Typ.	8.0×10^4 A/W
[Anode] Gain Typ.	1.0×10^6
[Anode] Dark Current (after 30min.) Typ.	1 nA
[Anode] Dark Current (after 30min.) Max.	50 nA
[Time Response] Rise Time Typ.	0.8 ns
[Time Response] Transit Time Typ.	9.0 ns

Contact us for more information.

 Literature

 Delivery

 Support

 Price

 Custom order

 Other

Contact us

Disclaimer 

Recommended products



High voltage power supply module C11152



D-type socket assembly E1761-04

No image

Photomultiplier 164-10